

Funded by:



SOLAR ENERGY
TECHNOLOGIES OFFICE
U.S. Department Of Energy



Solar PLUS: Physics-Aware Learning Based Scalable Modeling and Analytics for Solar Energy Integration

Qing Shen

Electrical and Computer Engineering

Stony Brook University

10/31/2023

PI: Peng Zhang (SBU)

Co-PIs: Xiangqi Zhu, Barry Mather (NREL), Yuzhang Lin (NYU)
Yue Zhao, Xin Wang, Yifan Zhou (SBU)

- **Challenges:**

Massive integration of solar PV generation makes it prohibitively difficult to perform accurate transient/dynamic analyses:

- Exhaustive physical models of all subsystems
- Astronomical contingencies and solar generation scenarios

- **Our solution:**

Ultra-scalable modeling and analytics of both transient and dynamic behaviors of power grids with solar PVs at all grid levels by exploiting the physics-aware machine learning:


- Accurately represent system behaviors at all levels
- Identify security risks under infinite PV scenarios in grid operations

Solar PLUS Overview


The proposed project includes three main parts:

- 1) Physical model library
- 2) AI-enabled scalable modeling
- 3) AI-enabled scalable analytics


Physical Model Library: Representative BTM
Load and PV Compositions



Ultra-Scalable Modeling:
Physics-Neural ODEs for Potentially Modeling
1M+ Devices



Ultra-Scalable Analytics:
Dynamic Verification for Infinite Uncertain Scenarios
Online Trans/Dynamic Analysis for Potentially
Assessing 1k+ Contingencies




Physical Model Library

- **Goals:** a high-fidelity model library of BTM PV and loads based on real-world system information
- **Accomplishment:** Validated **library** with **10+ types of load and PV models**

Benefits:

- Provide a **substantial coverage** for the dynamic models of the BTM generations and loads under different simulation scenarios
- Effectively tackle the **distribution system data-insufficiency** problem by serving as a high-fidelity training data synthesizer for data-driven modeling development.

Physical Model Library: Representative BTM Load and PV Compositions



- **Goal:**

Develop an advanced Neural ODE model to accurately track continuous system operational states under missing/noise data.

- **Variational Stochastic Differential Networks (VSDN) model :**

- Generates continuous state trajectories from discrete data samples.
- Generative model: can recurrently predict the future values of the sequence.
- Inference model: filters out the noise and shares the ODE and drift functions.





Fig 2.2: Block diagram of the filtering inference model used for experiments [1]

[1] Liu, Yingru, et al. "Continuous-time stochastic differential networks for irregular time series modeling." *Neural Information Processing: 28th International Conference, ICONIP 2021, Sanur, Bali, Indonesia, December 8–12, 2021, Proceedings, Part V* 28. Springer International Publishing, 2021.

[2] De Brouwer, Edward, et al. "GRU-ODE-Bayes: Continuous modeling of sporadically-observed time series." *Advances in neural information processing systems* 32 (2019)

Experimental Results

Experiments were performed on SETO 1001-bus 14DG microgrid system, developed by SBU team.




% noise	% missing data	RMSE	MAE	MAPE
0%	0%	0.0097	0.0042	0.0201
	30%	0.0414	0.0124	0.0610
	50%	0.0586	0.0168	0.0973
1%	0%	0.0122	0.0074	0.0271
	30%	0.0421	0.0152	0.0669
	50%	0.059	0.0192	0.1021
5%	0%	0.0381	0.0270	0.0848
	30%	0.0575	0.0344	0.1313
	50%	0.0695	0.0361	0.1523

Fig 2.2: Topology of the SETO 1001-bus 14-DG system


Table 2.1: Error performance metrics of VSDN model on 1001-bus data

Experimental Results


- Predicted mean of node voltage trajectories of node 632 of 1001-bus data for different scenarios



No missing samples, no noise



30% missing samples, 1% noise






50% missing samples, 5% noise

AI-enabled scalable analytics: Neuro-Reachability

How to verify uncertain dynamics with data-driven system models?




Neuro-Reachability: conformance-empowered reachable dynamics




Experiments and Validation

- **Test system:** 1001-bus transmission-distribution system
 - 7 distribution grids and 14 IBRs
 - Each IBR has a double-loop droop controller
 - Grid 6 and 7 are modeled by ODE-Net
- Reachable set under 10% uncertainty from each PV.




Without fault


Under the short-circuit fault




System frequency



PV output voltage



PV output power



PV output voltage

■ Data-Driven ReachSet
■ Model-Driven ReachSet

ODE-Net-enabled **neuro-reachability** conforms with the model-driven reachable sets → **A data-driven tool for verifying power grid dynamics** with both renewable uncertainties and unidentified subsystem models

AI-enabled scalable analytics: Neuro-Awareness

How to track dynamics of the system with unidentified subsystems?




Neuro-Awareness: Data-driven dynamic state estimation(DSE)

Challenges:

- Complete physics model of the whole systems may not always be attainable


Contributions:

- Neural dynamic state estimation** (Neuro-DSE) for Networked Microgrids with partially unidentified subsystems by integrating ODE-Net into Kalman filters.




Experiments and Validation

- **Test system:** 33-bus microgrid system
 - 5 grid forming based IBRs
 - Each IBR has a double-loop droop controller
 - Microgrid 4 is modeled by ODE-Net
- ODE-Net under 20% uncertainties of DER power input.




Simulation validates the effectiveness of Neuro-DSE under different noise levels



Integrating Learning and Physics based Computation for Fast Online Transient Analysis


- **Goal:** to accelerate the simulation of full power system transient trajectories.
 - Key: One predictor is trained for each generator.
- Replace the time-consuming dynamic computation of the generators with trained predictors
- Retain the time-efficient algebraic computation of solving AC-PF
- **Key Advantages**
 - **Scalability** : independent complexity
 - **No re-training**: agnostic to changes
 - **Flexible training strategies**:— joint, local, and singular – allowing different trade-offs between offline training complexity and online testing accuracy.



Iteratively alternates between calling all the trained predictors, solve AC-PFs and update inputs collectively.

Performance Evaluation

- We simulated 2,460 N – 2 contingencies in a 68 bus system, collected the simulated trajectories.
- Excellent performance in both accuracy and computation speed is demonstrated.



68-bus 16-generator system.

TABLE II: Computational Efficiency

Model	Offline Training time [min]	Offline Compute Memory [MB]	Online Compute Time [s]	Online Compute Memory [MB]
Singular	229	2245	2.16	1545
Local	767	2247	2.16	1545
Joint	2609	2941	2.16	1545
Numerical	-	-	19.9	269

TABLE I: Performance Comparison of Training Strategies

Training Strategy	Avg. RMSE	Avg. Relative RMSE
Joint	$3.631 \cdot 10^{-3}$	$4.056 \cdot 10^{-2}$
Local	$5.372 \cdot 10^{-3}$	$5.684 \cdot 10^{-2}$
Singular	$8.720 \cdot 10^{-3}$	$8.861 \cdot 10^{-2}$

J. Li, Y. Zhao, and M. Yue, "Integrating learning and physics based computation for fast online transient analysis," Proc. IEEE Conference on Innovative Smart Grid Technologies (ISGT), 2023.

This presentation may have proprietary information and is protected from public release.

